Data sheet: Fillogy Auto S (Art. 308174)

Description

- compact turn table version with collecting function
- alternatively can be equipped with transition plate for connecting,
- a conveyor belt, transition plate is included in the delivery
- table version, optionally also available with trolley set
- especially suitable for containers with a small opening diameter

Main field of application: semi-automated filling of containers between 2 to 500 grams

Customer benefit

Working with a turntable allows the process chain to be shortened in terms of time by integrating or connecting further production steps such as:

- glass feeding

- screwing
- labeling

Operating conditions

Hours of operation per day:	8
Days of operation per week:	5
Ambient temperature:	10 - 40°C

Technical Data

Nominal voltage:	24 V DC
Power consumption:	25 - 35 W
Rotation speed:	0,4 - 4,5 U/min (adjustable)
Standard sensor type:	capazitive
Diameter of container opening:	>= 8,0 mm
Storage space:	35 x 500 g Glass (15 empty + 20 full)
	45 x 250 g Glass (19 empty + 26 full)
Diameter turntable:	635 mm
Load-bearing capacity:	20,0 kg
Footage:	Width 635 mm x Depth 870 mm
Total Height:	655 mm / 1,385mm with frame
Work height:	flexible / 875 mm with frame
Weight:	24 kg (without power supply)

Further automation options

Connection of a collection turn table or conveyor belt for further production steps such as lidding and labelling.

